

LetsaLiner

BY 
LE TSA





DESIGNED WITH TECHNOLOGY


Long lasting polymer that is outdoor resistant and nonabsorbent.

PRODUCT'S STRENGTHS

It is a very versatile product, easy to handle, easy to install, easy to cut, anticorrosive, hygienic, low cost and resistant.

USES

Letsa Liner: is very versatile product, use it on any construction, roofs and walls.



LetsaLiner
BY 

TECHNICAL INFO

Letsa Liner is an acrylic-polyester laminated plastic reinforced with fiberglass, suitable for hospitals, shopping malls, fake walls, fake ceilings, poultry and pig farms.

AVAILABLE COLORS



White

PROFILE

LA 75



	ASTM NORMS	M.U.	VALUE
PHYSICAL PROPERTIES			
Thickness		bsm-25	2.2
Yellowing	D-195		No Change
Weight by m2 +/- 10%		kg/m ²	3
MECHANICAL PROPERTIES			
Bending resistance	D-790	PSI	1,118.79
Bending coefficient	D-790	PSI	39,864.07
Tension resistance	D-638	PSI	510.12
Bending coefficient	D-638	PSI	51,042.88
Impact resistance	D-256	PSI	10.01
CHEMICAL PROPERTIES			
Concentrated acids 15%	Sulfuric		No change
	Acetic		No change
	Hydrochloric		No change
	Nitric		No change
Bases	Ammonia		No change
	Sodium		No change
Solvents	Thinner		No change
	Gasoline		No change
OTHER PROPERTIES			
Barcol hardness	D-5261		50-53
Shot-S hardness			90



Because of its excellent functionality, LetsaLiner has been well received in damp and warm countries.

When installed, LetsaLiner work as a temperature and acoustic insulator.

LetsaLiner
UN PRODUCTO DE **LETSA**

HANDLING AND STORAGE:

You should consider the following storage indications regarding the LetsaLiner sheets when receiving merchandise from LETSA or any other delivery company. Please check the cargo with its shipping number in order to detect any possible anomaly or damage.

When lifting packages with forklifts, the forks must be at a 1.60 m distance. To avoid damaging the sheets, never handle open packages. Transport slowly in irregular roads in order to avoid any kind of folding in the sheets.

If the sheet measures over 3 m, we recommend lifting with 2 or more individuals from only one side to avoid folding. Never lift the sheets by its ends or horizontally, it is difficult and dangerous.

Packages must be stored over the floor at a sufficient height in order to allow air flow and prevent water leaks.

If not installed immediately, the sheets must be stored near the installation place and over a firm surface to prevent any kind of damage.

If while storing, the sheet makes contact with dust do not worry, just take a damp towel and clean the surface.



letsa .mx

 **Km 1.5 Carretera Antigua San Isidro Mazatepec,**
San Agustin, Mpio Tlajomulco de Zuñiga, Jalisco, C.P. 45640

 **33 1011 3622**

01 (33) 3686 0765, 01 (33) 3686 0674
01 (33) 3686 2028, 01 (33) 3686 1065